

D1xB2XH1 UL1971 Auto Sync Cl D1 86cd Strobe

The explosion proof D1xB2XH1 is an auto-synchronizing Xenon Strobe warning light / beacon tested to UL1971. UL/cUL/ULC approved for Class I/II Div 1, Class I Zone 1/Zone 21 for gas and dust environments.

The lightweight, marine grade, enclosure has been designed to create the optimal fire signal suitable for public mode fire alarm, ADA compliant, hearing impaired applications. Its innovative construction includes both conduit or surface mounting capabilities – without the need for any additional accessories. For complete flexibility an optional stainless-steel bracket enables the explosion proof warning light to be rotated and positioned in any orientation.

Multiple D1xB2XH1 units will auto-synchronize when powered from the same power source; removing the need for any additional sync modules on the circuit.

Features

- Public mode fire use UL1971 & CAN/ULC-S526
- Auto synchronized as per UL1971
- 86.37cd – UL1971 Public mode fire
- Operating current only 635mA
- In rush limited to 817mA for 5ms
- Choice of four flash rates
- Marine grade aluminum enclosure
- Ingress Type 4/4X/3R/13, IP66
- High impact Borosilicate glass lens
- Duplicate, pluggable terminations
- Diode protected for supervised circuits
- Conduit mount via 3/4" NPT entry
- Surface mount via user installed lugs
- Dual 3/4" NPT and dual M20 side entries
- Supplied with stopping plugs
- Optional multi-position wall bracket


Approvals

- UL/cUL File ref: E245313
- CSFM listing: 7300-2279:0507

Coding

- NEC: Class I Div 1 Group ABCD T5 Ta -55°C to +80°C
Class I Div 1 Group ABCD T6 Ta -55°C to +60°C
- CEC: Class I Div 1 Group CD T5 Ta -55°C to +80°C
Class I Div 1 Group CD T6 Ta -55°C to +60°C
- NEC / CEC: Class II Div 1 Group EFG T4A Ta -55°C to +80°C
Class II Div 1 Group EFG T5 Ta -55°C to +65°C
Class II Div 1 Group EFG T6 Ta -55°C to +50°C
Class III Div 1 Ta -55°C to +80°C
- NEC: Class I Zone 1 AEx db IIC T5 Ta -55°C to +80°C
Class I Zone 1 AEx db IIC T6 Ta -55°C to +60°C
Zone 21 AEx tb IIIC 107°C Ta -55°C to +80°C
- CEC: Ex db IIC T5 Ta -55°C to +80°C
Ex db IIC T6 Ta -55°C to +60°C
Ex tb IIIC 107°C Ta -55°C to +80°C





Specification

Source:	Xenon Strobe
Energy:	10 Joules
Modes:	1Hz flash (60 fpm) 1.3Hz flash (80 fpm) 1.5Hz flash (90 fpm) Double flash (120 fpm)
Eff. Intensity cd:	86.37 cd UL1971 Public mode fire
Peak Intensity cd:	1,000,000 cd
Synchronization:	Flash rates synchronize for a minimum of 2 hours per UL1971
Voltage:	24V dc (20-28V dc)
In-rush:	<817mA within 5ms @ 24Vdc
Ingress protection:	IP rating per EN60529:IP66 Type rating per UL50E/NEMA250:4/4X/3R/13
Enclosure material:	Marine grade LM6 aluminum alloy
Enclosure color:	Red (RAL3000)
Lens material:	High impact Borosilicate glass
Cable entries:	2 x 3/4"NPT, 2 x M20x1.5, 1 x 3/4"NPT
Stopping plugs:	Nickel plated brass plugs included
Terminals:	0.5 - 2.5mm ² (20-14 AWG)
Line monitoring:	Blocking diode included EOL can be factory or user installed
Operating temp:	-55 to +80°C [-67° to +176°F]
Storage temp:	-55 to +80°C [-67° to +176°F]
Relative humidity:	95% - Additional tropicalisation is recommended for applications where both high relative humidity and high ambient temperatures exist
Weight:	3.2kg/7.1lbs

Part Codes

Part Code:	Ident.:	Description:
Product type:	D1xB2	Explosion proof warning light
Type:	XH1	Xenon Strobe Beacon 10 Joule 86.37cd
Voltage:	DC024	24V dc (20-28Vdc)
Cable entries: [e]	M	2 x 3/4" NPT 2 x M20x1.5 1 x 3/4" NPT
Stopping plug material: [m]	N	Nickel plated brass
Lens guard & tag: [s]	0	No lens Guard
	5	No lens guard with Equip. Tag
Version: [v]	H1	UL, cUL, ULC - Class I/II Div 1, Class I Zone 1/Zone 21 - UL1971 & CAN/ULC-S526
Enclosure: [x]	R	Red RAL3000
Lens colour: [y]	C	Clear
e.g:	D1xB2XH1DC024MNOH1R/Cstopping plugs, UL, cUL approved - UL1971 Red enclosure with Clear lens	
Accessories:	SP77- Multi angle wall bracket 304 Stainless Steel 0001-A2- Multi angle wall bracket 316 Stainless Steel R SP77- 0001-A4-R	
Spares:	SP77- 0002 Xenon flash tube assembly SP77- 0003 XH1 PCBA including flash tube SP77- 0015-R Pack of 2 x Surface Mount Lugs Red SP77- 0016-R Pack of 2 x Bracket mount hole plugs Red	

Current Consumption

Nominal Voltage:	Voltage range:	Flash Rate setting:	Nominal operating current:	In rush:
24V dc	20-28V dc	1Hz (60fpm)	635mA	<817mA <5ms
		1.3Hz (80 fpm)	695mA	
		1.5Hz (90fpm)	700mA	
		Double (120fpm)	580mA	