



Respiratory Protection ESCAPE DEVICES WITH FILTER

Blitz 10





Respiratory Protection ESCAPE DEVICES WITH FILTER

Blitz 10

BLITZ 10 is an escape device with ABEK filter, equipped with a mouthpiece and a nose clip. It protects against industrial gases and vapours.



DESCRIPTION

BLITZ 10 protects respiratory organs from organic vapours and gases with a boiling point higher than 65 °C, inorganic vapours and gases, acidic and basic vapours and gases.

- Protection is limited with respect to compounds with a boiling point lower than 65°C and in highly toxic concentrations.
- The device does not protect from carbon monoxide or oxygen lack, since it does not provide oxygen.
- The duration of respirator BLITZ 10 is 10 minutes.

MAIN FEATURES



PERFORMANCES



Lightness



Adaptability



Easy donning



Sturdiness



Shelf life



APPLICATION FIELDS



Petrochemical



Industrial



Chemical-Pharmaceutical Industry

BREATHING RESISTANCE

The test is conducted with continuous flow of air at 95 l/min at a temperature of 20 ° C and relative humidity of 70% according to the following table:

Class	Weight of the device (less than)	Resistance mbar Maximum inspiratory (DIN 58647-7 requirement)	Resistance mbar Maximum expiratory
10 min	600	8	5
Average values of 20 tested samples		4,1	3,4

FILTER CAPACITY

The test is conducted with continuous flow of air at 30 l/min at a temperature of 20° C and relative humidity of 70% according to the following table:

Type	Testing gas	Concentration	Breaking time	Typical values
A	Cyclohexane (C6H12)	2500	10 min	>10 min
B	Chlorine (Cl2)	2500	10 min	>10 min
B	Hydrogen sulphide (H2S)	2500	10 min	>10 min
B	Hydrogen sulphide (H2S)	10000	3 min	>3 min
B	Hydrocyanidric acid (HCN)	2500	10 min	>10 min
E	Sulphur dioxide (SO2)	2500	10 min	>10 min
K	Ammonia (NH3)	2500	10 min	>10 min

MATERIALS

- Box: Plastic
- Filter: Plastic
- Mouthpiece: Rubber
- Filtering element: Active carbon and TNT

WEIGHT

- Product ready to use: 150 g
- Product with carrying case: 220 g

STORAGE

- Shelf life: 6 years, in its original packaging. The expiry date is shown on the label of the device and also on the packaging
- Temperature: between -10°C and +50°C
- Humidity: < 90%.



DONNING AND USING

For Fitting the steps are: Break the seal and open the pack by pulling the tab on its cover - Take the filter with the mouthpiece - Put the mouthpiece in your mouth and close your lips around it - Put the clip on your nose and breathe through your mouth only - Do not speak during use - Leave the dangerous area.

- The opening is simple and fast, the donning is instinctive, in order to immediately isolate the user from the external polluted environment.
- Blitz 10 has a sealing system that verifies that no tampering, falls or accidental openings may have occurred.
- BLITZ 10 is very small, can be put in the pocket or can be fastened to the belt.

CERTIFICATIONS

Approved in accordance with DIN 58647-7.
Certified according to European Regulation 2016/425

ITEM NO.

4333 7010